



Installation Instructions

Turbo Oil Line Feed Kit Ford FG XR6 Turbo

PFEOSFDTBO-FG

Included Items	QTY
-04AN Stainless Braided Oil Feed Line With Heat Sleeve	1
-04AN Stainless Braided Oil Feed Line	1
Stainless Steel Banjo To -04AN Fitting	1
Stainless Steel 7/16"-24 To -04AN Fitting	1
Stainless Steel M12 x 1.50mm To -04AN Fitting (Used For F6 Models)	1
30 Micron Billet Aluminium Oil Filter -04AN	1
Aluminium Crush Washers	4

WARNING: PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. PROFLOW WILL NOT BE RESPONSIBLE FOR ANY DAMAGE AS A RESULT OF THE INCORRECT INSTALLATION OF THIS PRODUCT. IT IS RECOMMENDED THAT A QUALIFIED AUTOMOTIVE TECHNICIAN PERFORMS THIS INSTALLATION.

1. Following the factory service manual of your vehicle, disassemble the factory turbo oil feed line.
2. Ensure to keep all fasteners/gaskets and other factory components as they may be reused for reinstallation of your new turbo oil feed line.
3. Install the steel banjo fitting into the engine block using the factory banjo bolt, ensuring you are using new copper washers which are not supplied (PFE179).
4. If installing on a F6 model, install the supplied M12 x 1.50mm fitting into the engine block with new crush washers. Otherwise, this fitting is **not** used.
5. Install the 7/16"-24 fitting into the top of the turbo.
6. Install the 30 Micron oil filter in between both -04AN oil feed lines, one coming from the turbo and the other line coming from the block. The oil line with the heat shield sleeve attached should be connected to the turbo side.
7. Ensure the stainless oil feed lines are away from moving parts such as the drivebelt. Purchase the Proflow oil and water line feed bracket for a neat solution (PFEOSFDBKT).
8. Ensure all fittings and hose assemblies are tightened before starting the engine.
9. Start the engine and check for any leaks coming from the oil line assembly before driving the vehicle.



PROFLOW LIMITED WARRANTY

PROFLOW.COM.AU

EMAIL: sales@proflow.com.au
PHONE: 1300 879 879

This Proflow product is warranted to be free from defects in materials and workmanship for a period of one year from the original date of purchase. No warranty claim will be valid without authentic, dated proof of purchase. This warranty is to the original retail purchaser and none other and is available directly from Proflow and not through any point of distribution or purchase.