



Installation Instructions

Turbo Oil Drain Kit Ford Barra BA/BF/FG

PFEOSODFD-10

Included Items	QTY
PFE400R-10BK Black Push Lock Hose -10AN (5/8") 0.5m Length	1
PFE692-10BK Turbo Oil Drain Adapter -10AN Male	1
PFE692-10BK-FD Ford Block Oil Drain Adapter -10AN male	1
PFE513-10BK 90 Degree Fitting Hose End Full Flow -10AN to 5/8" Barb	2
PFE513-10BK 90 Degree Fitting Hose End Full Flow -10AN to 5/8" Barb	2
Stainless Steel Worm Gear Hose Clamp 18-25mm ID	1

WARNING: PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. PROFLOW WILL NOT BE RESPONSIBLE FOR ANY DAMAGE AS A RESULT OF THE INCORRECT INSTALLATION OF THIS PRODUCT. IT IS RECOMMENDED THAT A QUALIFIED AUTOMOTIVE TECHNICIAN PERFORMS THIS INSTALLATION.

1. Following the factory service manual of your vehicle, disassemble the factory turbo oil drain plumbing system from the block and turbo.
2. Ensure to keep all fasteners/gaskets as these may need to be reused when reinstalling your components.
3. Install the block oil drain adapter (the one with the larger O-ring) into the block after cleaning the sealing surface. Ensure the O-ring is seated correctly on the bottom of the fitting.
4. Use the factory bolts from the old turbo oil drain to fasten the new -10AN male adapter. It is recommended to use a light grade Loctite on the bolts to avoid them from vibrating loose.
5. Install the last turbo oil drain adapter on the turbo and repeat step 4.
6. Fasten the 45-degree hose end fitting to the block oil drain adapter and the 90-degree hose end to the turbo side.
7. Connect both oil drains with the provided push lock hose and fasten both ends of the hose with the supplied stainless-steel clamps.
Note: if you are having difficulties pushing on the hose to the barbs, you may place the hose in hot water to soften it before trying again.
8. Ensure all fittings and hose assemblies are tightened before starting the engine.
9. Start the engine and check for any leaks coming from the turbo oil drain assembly before driving the vehicle.



PROFLOW LIMITED WARRANTY

PROFLOW.COM.AU

EMAIL: sales@proflow.com.au
PHONE: 1300 879 879

This Proflow product is warranted to be free from defects in materials and workmanship for a period of one year from the original date of purchase. No warranty claim will be valid without authentic, dated proof of purchase. This warranty is to the original retail purchaser and none other and is available directly from Proflow and not through any point of distribution or purchase.