



Installation Instructions

LS Remote Oil Block Adapter

PFEOSR-LS90

Included Items	QTY
PFEOSR-LS90 Remote Oil Block Adapter	1
PFE920-10BK -10AN ORB to -10AN Straight Fitting	2
ISO3601-1 (18.72mm x 2.62mm) O-Ring	2
M8 x 30mm Socket Head Cap Screw ISO 4762	2
M8 Flat Washer ISO 7089	2
M6 x 30mm Socket Head Cap Screw ISO 4762	1
M6 Flat Washer ISO 7089	1

WARNING: PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. PROFLOW WILL NOT BE RESPONSIBLE FOR ANY DAMAGE AS A RESULT OF THE INCORRECT INSTALLATION OF THIS PRODUCT. IT IS RECOMMENDED THAT A QUALIFIED AUTOMOTIVE TECHNICIAN PERFORMS THIS INSTALLATION.

Proflow's billet aluminium LS oil block adapter allows you to plumb an external oil filter setup, which is typically used on engine swaps where clearance is an issue and room is limited. This adapter will fit most aftermarket LS fabricated oil pans and fastens using three bolts that mounts directly to the block. Direct fit for RTS oil pan # RTS-3000.

This 90 degree positioned remote oil filter block comes with 2 -10AN ports with two -10AN ORB fittings, allowing you to directly screw on your choice of hose and size for your sepecific application. Use the port closer to the front of the block as the filter inlet, which will be the oil coming out the block flowing into the filter.

When fitting this adapter to the bottom of the block, ensure both O-Rings are seated correctly in their grooves. It is recommneded that a light grade thread locker is used on each bolt to ensure they do not come loose due to vibration.



PROFLOW LIMITED WARRANTY

PROFLOW.COM.AU

EMAIL: sales@proflow.com.au
PHONE: 1300 879 879

This Proflow product is warranted to be free from defects in materials and workmanship for a period of one year from the original date of purchase. No warranty claim will be valid without authentic, dated proof of purchase. This warranty is to the original retail purchaser and none other and is available directly from Proflow and not through any point of distribution or purchase.