



# Instruction Manual

## TUBING STRAIGHTENER

### PFETUBSTR

**WARNING:** PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. PROFLOW WILL NOT BE RESPONSIBLE FOR ANY DAMAGE AS A RESULT OF THE INCORRECT USE OF THIS PRODUCT.

Included Items	QTY
Tubing Straightener For 3/16" to 1/2" Tube	1

Proflow's tube straightening tool is designed to straighten out coils of tubing quickly and can be used with any hollow tubing. It uses 5 nylon rollers to straighten the tube out which will not damage the surface of the tubing and can be used with tube OD's from 3/16" to 1/2".

1. Mount the device in a vice to make it easier to use.
2. Straighten the start of the tubing from the coil by hand first so it can be placed in the straightener with ease.
3. Open the nylon rollers by unscrewing the handle on top of the device allowing enough space for the tubing to fit.
4. Insert the tubing between the top and bottom rollers and start feeding the tube through the straightener. Tighten the clamp down until the rollers are touching the tube. Push the tube back and fourth slowly through the rollers to start straightening the tube.
5. Rotate the tubing while passing it back and fourth through the rollers to ensure the tube is straight in both directions.
6. Gradually tighten the top handle to apply more pressure to the tubing so it becomes as straight as possible.



#### PROFLOW LIMITED WARRANTY

**PROFLOW.COM.AU**

EMAIL: sales@proflow.com.au  
PHONE: 1300 879 879

This Proflow product is warranted to be free from defects in materials and workmanship for a period of one year from the original date of purchase. No warranty claim will be valid without authentic, dated proof of purchase. This warranty is to the original retail purchaser and none other and is available directly from Proflow and not through any point of distribution or purchase.